Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200._Standard must be consulted for specific requirements.

U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072



IDENTITY (As Used on Label and List) Natural Magic Herbal Odor Blas	ter	Note: Blank spac information	es are not permit is available, the	space must be	ns not appli marked to i	ndicate the
Section I	· CCI	 				1.
Manufacturer's Name		Emergency Telep	hone Number			
Osmegen Incorporated		(610) 865-				
Address (Number, Street, City, State, and ZIP Code)		Telephone Numb		,		
732 E. Goepp St.		(610) 865-3	3393			
		Date Prepared				
Dethlehem, PA 18018		October 30.				
		Signature of Prep	arer (optional)			
Section II — Hazardous Ingredients/Ident	tity Information					
Hazardous Components (Specific Chemical Identity; Co	Common Name(s))	OSHA PEL	ACGIH TLV	Other L Recomm		% (optic
Proprietary Formula						
All components used to relative	·		1 . 1	·		
All components used to make thi	is product a	re considere	a to be sa	re.		
through normal use of product.						·
Section III — Physical/Chemical Character	ristics					
Section III — Physical/Chemical Character		Specific Gravity (H ₂	O - 1)			
		Specific Gravity (H ₂	O - 1)			
Rolling Point			O = 1)			
toiling Point 100°F 212°F apor Pressure (mm Hg.) 11/A		1.005	0 - 1)			
toiling Point 100°F 212°F apor Pressure (mm Hg.) 11/A		1.005 Melting Point	0 - 1)			
tolling Point 100°F 212°F apor Pressure (mm Hg.)		1,005 Melting Point N/A				
toiling Point 100°F 212°F apor Pressure (mm Hg.) 11 / A apor Density (AIR = 1)		1,005 Melting Point N/A Evaporation Rate				
Soiling Point 100°F 212°F apor Pressure (mm Hg.) N/A apor Density (AIR = 1) N/A Cubility in Water YES		1,005 Melting Point N/A Evaporation Rate				
Solling Point 100°F 212°F apor Pressure (mm Hg.) 15/ A apor Density (AIR = 1) 15/ A olubility in Water		1,005 Melting Point N/A Evaporation Rate				
toiling Point 100°F 212°F apor Pressure (mm Hg.) N/A apor Density (AIR = 1) N/A ofubility in Water YES		1,005 Melting Point N/A Evaporation Rate				
koling Point i 00°F 212°F apor Pressure (mm Hg.) ii/A apor Density (AIR = 1) ii/A Dotubility in Water YES ppearance and Odor NATURAL HERBAL		1,005 Melting Point N/A Evaporation Rate				
koling Point i 00°F 212°F apor Pressure (mm Hg.) ii /A Brick Columbia in the columbia in t	Pata	1.005 Melting Point If / A Evaporation Rate Butyl Acetate = 1)			İUFL	
toiling Point 1.00°F 212°F apor Pressure (mm Hg.) IV/A IV/A IV/A Outbilly in Water YES Popearance and Odor NATURAL HERBAL ection IV — Fire and Explosion Hazard Diash Point (Method Used)	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		LEL	UEL 17/2	
Solling Point 100°F 212°F apor Pressure (mm Hg.) N/A apor Density (AIR = 1) N/A olubility in Water YES ppearance and Odor NATURAL HERBAL ection IV — Fire and Explosion Hazard Diash Point (Method Used)	eata F	1.005 Melting Point If / A Evaporation Rate Butyl Acetate = 1)		LEL	UEL IV/#	
toiling Point i 00°F 212°F apor Pressure (mm Hg.) ii/A apor Density (AIR = 1) ii/A blubility in Water YES ppearance and Odor NATURAL HERBAL ection IV — Fire and Explosion Hazard Diash Point (Method Used) ii/A itinguishing Media	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		
toiling Point 1.00°F 212°F apor Pressure (mm Hg.) N/A N/A Outbilly in Water YES Popearance and Odor NATURAL HERBAL ection IV — Fire and Explosion Hazard Di ash Point (Method Used) N/A tinguishing Media N/A	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		
tolling Point 100°F 212°F apor Pressure (mm Hg.) 100°A 100 A	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		
toiling Point 1.00°F 212°F apor Pressure (mm Hg.) N/A N/A Outbilly in Water YES Popearance and Odor NATURAL HERBAL ection IV — Fire and Explosion Hazard Di ash Point (Method Used) N/A tinguishing Media N/A	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		
tolling Point 100°F 212°F apor Pressure (mm Hg.) 100°A 100 A	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		
tolling Point 100°F 212°F apor Pressure (mm Hg.) 100°A 100 A	eata F	1.005 Melting Point N/A Exaporation Rate (Buryl Acetate = 1)		1		

	- Reactivity Da	ta .		A
Slavility	Unstable		Conditions to Avoid	-1
	Stable	X		1
Incompatibility	(Materials to Avoid			
Hazardous Dec	omposition or Byprod	ducts		
Hazardous	May Occur		Conditions to Avoid	
Polymerization	Will Not Occur			
C==1:== 10	<u> </u>	У.		
Route(s) of Entr	- Health Hazard	alation?	Skin?	ingestion?
	NO HA		REHOVE WITH WATER	NONE
realin mazaros	(Acute and Chronic)			
N/A				
Carcinogenicity: NONE	TM M		IARC Monographs?	OSHA Regulated?
				· · · · · · · · · · · · · · · · · · ·
Signs and Symp	toms of Exposure			
NONE				
Medical Conditio	ns			
Generally Aggrav	rated by Exposure			
NONE	E-TRIB			
	First Aid Procedures	TER,	REMOVE CONTACT LENSES.	
mergency and EYES - i			REMOVE CONTACT LENSES.	
EYES - E CALL PHY Section VII -	/SICIAN IF IF - Precautions f	RITAT	FION PERSISTS. e Handling and Use	
EYES - E CALL PHY Section VII -	SICIAN IF IN	RITAT	FION PERSISTS. e Handling and Use	
EYES - E CALL PHY Section VII -	SICIAN IF IN Precautions for in Case Material	RITAT or Safe Is Releas	FION PERSISTS. e Handling and Use sed or Spilled	
EYES - E CALL PHY Section VII -	/SICIAN IF IF - Precautions f	RITAT or Safe Is Releas	FION PERSISTS. e Handling and Use sed or Spilled	
EMERGENCY and EYES - I CALL PHY Section VII - ROUTINE ROUTINE	SICIAN IF IN Precautions for in Case Material CLEAN UP WIT	RITAT or Safe Is Releas	FION PERSISTS. e Handling and Use sed or Spilled	
EMERGENCY and EYES - I CALL PHY Section VII - ROUTINE ROUTINE	CSICIAN IF IN Precautions for in Case Material CLEAN UP WIT	RITAT or Safe Is Releas	FION PERSISTS. e Handling and Use sed or Spilled	
EMERGENCY and EYES - I EYES - I EYES - I CALL PIN Section VII - Reps to Be Take ROUTINE Vaste Disposal N NO KNOWN	(SICIAN IF IN Precautions for in Case Material CLEAN UP WITE Method REGULATION	RITAT Or Sale Is Releas TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
EMERGENCY and EYES - I EYES - I EYES - I CALL PIN Section VII - Reps to Be Take ROUTINE Vaste Disposal N NO KNOWN	SICIAN IF IN Precautions for in Case Material CLEAN UP WIT	RITAT Or Sale Is Releas TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
ETES - I ETES - I CALL PIN Section VII - Iteps to Be Take ROUTINE Vaste Disposal M NO KNOWN	(SICIAN IF IN Precautions for in Case Material CLEAN UP WITE Method REGULATION	RITAT Or Sale Is Releas TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
EYES - I CALL PIN Section VII - Itleps to Be Take ROUTINE Vaste Disposal N NO KNOWN recautions to Be NONE	(SICIAN IF IN Precautions for in Case Material CLEAN UP WIT Method I REGULA'TION Taken in Handling	RITAT Or Sale Is Releas TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
EMERGENCY and EYES - I EYES - I CALL PHY Section VII - ROUTINE ROUTINE Vaste Disposal M NO KNOWN RECAUTIONS to Be NONE	(SICIAN IF IN Precautions for in Case Material CLEAN UP WIT Method I REGULA'TION Taken in Handling	RITATION SAID	FION PERSISTS. e Handling and Use sed or Spilled FER	
EMERGENCY and EYES — I EYES — I EYES — I CALL PIIV Section VII — ROUTINE ROUTINE ROUTINE NO KNOWN TO BE NONE TO BE NOTE T	/SICIAN IF IN Precautions for in Case Material CLEAN UP WIT Method I REGULATION Taken in Handling	RRITAT OF Safe Is Release TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
ETES - I ETES - I CALL PII) Section VII - Itleps to Be Take ROUTINE Vaste Disposal N NO KNOWN recautions to Be NONE ther Precautions HONE	(SICIAN IF IN Precautions for in Case Material CLEAN UP WIT Method I REGULA'TION Taken in Handling	RRITAT OF Safe Is Release TH WAT	FION PERSISTS. e Handling and Use sed or Spilled FER	
EYES - I CALL PIN Section VII - Iteps to Be Take ROUTINE Vaste Disposal N NO KNOWN Recautions to Be NONE ther Precautions HONE ROUTINE Control VIII - ROUTINE	SICIAN IF IN Precautions f in Case Material CLEAN UP WIT Method REGULATION Taken in Handling Control Measurement (Specify Type) Local Exhaust	RRITAT OF Safe Is Release TH WAT	e Handling and Use sed or Spilled FER Special	
ETES - I ETES - I CALL PII) Section VII - Itleps to Be Take ROUTINE Vaste Disposal N NO KNOWN recautions to Be NONE ther Precautions HONE ection VIII - sepiratory Protect N/A ntiliation	Precautions f Precautions f Precautions f In In Case Material CLEAN UP WIT Method I REGULATION P Taken in Handling - Control Measuration (Specify Type) Local Exhaust IV/A	RITATION SAINTS RELEASE THE WATER AND Sto	PEON PERSISTS. e Handling and Use sed or Spilled FER Aring	
EYES - I CALL PIN Section VII - Iteps to Be Take ROUTINE Vaste Disposal N NO KNOWN recautions to Be NONE ther Precautions HONE ection VIII - espiratory Protect N/A ntilation	SICIAN IF IN Precautions f in Case Material CLEAN UP WIT Method REGULATION Taken in Handling Control Measurement (Specify Type) Local Exhaust	RITATION SAINTS RELEASE THE WATER AND Sto	e Handling and Use sed or Spilled FER sing Special N/A Other	
EYES - I EYES - I CALL PIN Section VII - Iteps to Be Take ROUTINE Vaste Disposal M NO KNOWN Recautions to Be NONE HONE ROUTINE HONE ROUTINE HONE ROUTINE ROUTI	ACTION IF IN Precautions for in Case Material CLEAN UP WIT Method I REGULATION Taken in Handling Control Measurion (Specify Type) Local Exhaust (General)	RRITAN OF Safe Is Release H WAT and Sto	e Handling and Use sed or Spilled FER fing Special N/A	